### STRETCH CODE OVERVIEW



**Town of Acton – Monday February 1st 2010** 

**Ian Finlayson – Department of Energy Resources** 

## Energy Codes in MA are changing

- New base energy code in July (IECC 2009)
  - Roughly 10% more energy efficient
- Towns and Cities can opt into the "Stretch Code" appendix
  - Approx 20% more energy efficient
     than IECC 2009 or ASHRAE 90.1-2007



Commercial bldgs. ASHRAE 90.1-2007 remains


## Residential based on 'Energy Star'

- Proven cost-effective program
  - 15% of new construction in MA
- Builder incentives/rebates
  - \$1,250/home for HERS 65 (energy star tier 2)
  - Up to \$8,000 for HERS <40</p>
  - Rebates on appliances,
     heating and cooling, lighting, etc.
- Builder training and materials
- Subsidized HERS raters



## New Homes – Energy Rating (HERS)

- Energy 'Performance' rating (like car MPG)
  - Uses <u>Home Energy Rating System</u> (HERS) Index
  - -70 or less < 3,000 sq ft.
  - -65 or less > 3,000 sq ft.
- Requires a certified HERS rater
  - Review building plans
  - Check insulation installation
  - Blower-door and duct testing
  - Thermal bypass Checklist





Please fill out the following form. You cannot save data typed into this form.

Please print your completed form if you would like a copy for your records.

Highlight Field




## ENERGY STAR Qualified Homes Thermal Bypass Inspection Checklist

Home Address:City				State:			
Thermal Bypass	Inspection Guidelines	Corrections Needed	Builder Verified	Rater Verified	N/A		
Overall Air Barrier and Thermal Barrier Alignment	Requirements: Insulation shall be installed in full contact with sealed interior and exterior air barrier except for alternate to interior air barrier under item no. 2 (Walls Adjoining Exterior Walls or Unconditioned Spaces)  All Climate Zones:						
	1.1 Overall Alignment Throughout Home						
	1.2 Garage Band Joist Air Barrier (at bays adjoining conditioned space)						
	1.3 Attic Eave Baffles Where Vents/Leakage Exist						
	Only at Climate Zones 4 and Higher:						
	1.4 Slab-edge Insulation (A maximum of 25% of the slab edge may be uninsulated in Climate Zones 4 and 5.)						
	Best Practices Encouraged, Not Req'd.:						
	1.5 Air Barrier At All Band Joists (Climate Zones 4 and higher)				$\vdash =$		
	1.6 Minimize Thermal Bridging (e.g., OVE framing, SIPs, ICFs)						
Walls Adjoining     Exterior Walls or     Unconditioned     Spaces	Requirements:  • Fully insulated wall aligned with air barrier at both interior and exterior, OR  • Alternate for Climate Zones 1 thru 3, sealed exterior air barrier aligned with RESNET Grade 1 insulation fully supported  • Continuous top and bottom plates or sealed blocking						
	2.1 Wall Behind Shower/Tub						
	2.2 Wall Behind Fireplace						
	2.3 Insulated Attic Slopes/Walls						
	2.4 Attic Knee Walls						
	2.5 Skylight Shaft Walls						
	2.6 Wall Adjoining Porch Roof						
	2.7 Staircase Walls						
	2.8 Double Walls						

## Home Additions – 2 options

- HERS index on just addition or whole house
  - -70 or less < 3,000 sq ft.
  - -65 or less > 3,000 sq ft.

- Prescriptive Path
  - Energy Star Windows
  - Base Code insulation and envelope (IECC 2009)
  - Thermal Bypass Checklist



## Home Renovations – 2 options


- Performance Path is easier
  - Easier HERS index requirement (mostly relevant for

gut-renovations)

- -85 or less < 2,000 sq ft.
- -80 or less > 2,000 sq ft.
- Prescriptive Path
  - Same as for additions
  - Energy Star Windows
  - IECC 2009 envelope & Thermal bypass checklist



## Why test Performance?



Design, Installation & Equipment all important.

- Blower-door test for air leakage
- Duct test for heating & AC
- Optional Infra-red test thermal barrier install.

Image source: http://www.pixelthermographics.co.uk/images/FrontJoinedIR.jpg

## Cost of Stretch code

- Cost effective and already proven in the voluntary market
  - Energy star 15% of all MA new residential in 2008

- Example homes show clear \$\$ savings
  - New 3-bed 2,700 ft<sup>2</sup> ranch
  - Rehab. urban triple-decker 3x 1,400 ft² units

# Example of Benefit-Cost Modeling: 2,672 square foot, 3-bedroom home

Task A – New Home				
HERS Index Modeled in REM/Rate	60 (energy use 40% below 2006 IECC code)			
Improvement Measures (changes relative to base case)	<ul> <li>Conditioned basement</li> <li>Foundation Walls R10 insulation</li> <li>Above grade walls R22 insulation</li> <li>Window U-factor .33</li> <li>Attic ceiling R38 cellulose insulation</li> <li>Slope ceiling R32 cellulose insulation</li> <li>Infiltration 4 ACH50</li> <li>Natural Gas Furnace 94 AFUE, 65kBtuh</li> <li>Central Air Conditioner 3 ton 15 SEER</li> <li>Domestic Hot Water .62 natural gas tank</li> <li>Programmable thermostat</li> <li>75% Fluorescent lighting</li> </ul>			
Improvement Costs	\$ 8,103			
Mortgage Interest Rate	5%			
Loan Term (Years)	30			
Annual Incremental Mortgage Payment	\$527			
Annual Energy Costs	\$ 3,103			
Annual Energy Savings from Baseline	\$1,364			
Annual Cash Flow Gain	\$ 837			

Note: This does not include the cost of a HERS rater (est. \$500-1200) or the savings from utility rebates (\$1,250) and Federal Tax Credits (up to \$4000).

## **COMMERCIAL STRETCH CODE**



## Commercial 'Stretch' Appendix

 Based on New Buildings Institute – 'Core Performance' Energy Code







<u>home</u>

codes

lighting

mechanical

<u>measured</u> performance

<u>about us</u>

careers

Related Sites:



ww.advancedbuildings.net

CORE PERFORMANCE CUIDE

### NBI-Supported Energy Codes

### **NBI Support of State and Local Jurisdictions**

Learn how NBI is working with cities and states to support development of strong energy requirements in building energy codes.

<u>Core Energy Code</u> is a code text that is ready for state and local adoption. Core Energy Code is available as either a mandatory of "<u>stretch code</u>" application and is formatted as a revision to Chapter 5 of the IECC. The document includes many of the Core Perfor and other measures proposed by NBI, AIA or US DOE for the 2012 IECC.

### Proposals to the 2012 IECC

NBI, the U.S. Department of Energy and the American Institute of Architects <u>have proposed comprehensive changes</u> to a national energy code for new commercial buildings, the International Energy Conservation Code (IECC), which would create buildings that about 25% more energy efficient. Read the <u>2012 IECC Proposal</u>, or a <u>Synopsis</u> of the proposed changes including the Reason Stat In addition, NBI and AIA are proposing additional revisions to requirements for <u>fenestration</u>, and <u>building envelope</u>.

### Massachusetts Adopts NBI-Supported Code

Core Performance has been adopted as part of a <u>stretch code</u> for Massachusetts. The new rules would make new commercial bu under 100,000 square feet up to 30% more energy efficient than current standards and reduce carbon emissions by nearly 40%.

### Codes and Standards for Advanced Energy Efficiency Buildings

## Commercial 'Stretch' Appendix

- Only New Commercial Buildings
- Only buildings or additions over 5,000 ft<sup>2</sup>
- 2 Options (depending on size)
  - Performance option 20% below Code
  - Prescriptive option for most building types
     5,000 100,000 ft2

## Commercial 'Stretch' Appendix

- Performance option
  - 20% below Code (ASHRAE 90.1-2007 appendix G)
  - all buildings over 100,000 ft<sup>2</sup>
  - Labs, Supermarkets, over 40,000 ft<sup>2</sup>
- Prescriptive option for most building types
  - 5,000 100,000 ft2
- Exemptions (comply with base code)
  - Special cases smaller than 40,000 ft<sup>2</sup>


## Fidelity Bank Corporate Office and Branch Case Study Leominster, MA


### **Advanced Building Features**

- · High Efficiency T-5 Pendant Lighting
- · Lighting Control Efficiency
- · Reduced Lighting Power Density
- · Efficient Site Lighting
- · Additional Wall Insulation
- · High Performance Glazing
- Efficient VAV RTU's, with ECM Motors
- Demand Control Ventilation
- · Part Load HVAC Efficiency Enhancements

### **Funded Utility Services Support**

- Early Life Cycle Cost Analysis
- · Integrated Design Team Approach
- Commissioning







### **Project Description**

The 47,000 SF Fidelity Bank Corporate Office and Branch was constructed as a design-build project in Leominster, MA. The four story building will provide office space plus a ground floor branch bank office. This project is acclaimed for its highly successful implementation of the national Advanced Buildings program. The project demonstrates the validity of the Advanced Buildings program assertions. The guideline cost effectively delivered even more than the expected 20% to 30% reduction in annual energy costs compared to a code based design.

#### **Envelope Improvements**

- · Walls: Added 3-1/2" batt insulation to planned 2" rigid.
- Glazing:
  - Upgrade U value from 0.42 to 0.31
  - Upgrade SHGC from 0.50 to 0.30
- · Projected envelope savings: \$1,500

### **Project Team**

Owner: Fidelity Bank Project Management: Habitat Advisory Group





### High Performance Building Design Uses 31% Less Energy

### **Savings Projection**


Annual Energy Savings: \$ 27,600

Additional Cost for Upgrades: \$100,622

 Utility Incentives:
 -\$ 66.587


 Net Owner Costs:
 \$ 34.035

31% Improvement Over Code



Payback with Incentives: Payback without Incentives: 1.2 years ROI: 83%

3.7 years ROL 27%



Annual Energy Costs

### **Lighting Savings Summary**

The lighting layout consisted mainly of T-5 pendants in open office areas, and the latest generation of recessed T-5 fixtures in the remaining areas.

Projected Lighting Savings: \$7,200






	Mass Energy Code	Advanced Buildings Criteria	Final Design	% Reduction
Lighting Power Density	1.34 w/SF	0.96 w/SF	0.86 w/SF	36%

Improved lighting quality while using less energy!

## Commercial 'Stretch' & LEED(v.3)


- LEED and Commercial 'Stretch' code are fully compatible
  - Both use ASHRAE 90.1-2007 app. G
     as the energy modeling baseline.



LEED also has non-energy requirements


## Code Compliance & Inspections

- Essentially the same as base code
- Code Official has the same authority
  - Same building inspections
  - Approves building documents,
     Energy Star and HERS rating or
     ASHRAE modeling as
     documentation of energy
- Certificate is required



## Training on new energy codes

- Covering both the IECC 2009 & Stretch code
- Provided free to all Code Officials
  - Includes IECC code book and Stretch appendix
- Provided at cost to building professionals
- Register online: <u>www.cetonline.org/Events/events.php</u>
  - Separate Commercial and Residential sessions
- Energy star homes training available for free: <u>www.energystarhomes.com/</u>
- Utilities offer commercial 'Core Performance' energy training



## Incentives available

- Towns/Cities Green Communities Program
  - Technical assistance available now
  - Larger grant round out soon
- Builders Energy Star & Utility Programs
  - Energy Star Residential
  - Utility Commercial
  - Federal \$2k/unitresidential tax credit



### www.mass.gov/Eeops/docs/dps/inf/appendix\_120\_aa\_jul09\_09\_final.pdf



Home > Public Safety Agencies > Massachusetts Department of Public Safety >

### Energy Conservation 'Appendix 120 AA' Approved

A code change proposal relating to energy conservation was approved by the BBRS at the May 12, 2009 meeting and will become an appendix to the MA State Building Code (<u>780 CMR</u>) on or about August 1, 2009. It is based on the *International Energy Conservation Code (IECC) 2009* and can be viewed by following the 1<sup>st</sup> link below. The 2<sup>nd</sup> link will take you to a two-page overview of this new appendix.

This appendix may be adopted by any municipality in the commonwealth, by decision of its governing body. In a city having a Plan D or Plan E charter the governing body shall be the city manager and the city council, and in any other city the mayor and city council. In towns the governing body shall be the board of selectmen. In order to be adopted, the appendix must be considered at an appropriate municipal public hearing, subject to the municipality's existing public notice provisions. If adopted by a municipality this appendix rather than 780 CMR 13, 34, 61, or 93, as applicable, shall govern.

Also at the May 12 meeting a concurrency period and a training policy were approved. Concurrency period is a period when <u>either</u> the new code <u>or</u> the existing code can be used but <u>not comingled</u>. The BBRS approved a concurrency period of 6 months to a maximum of 12 months, with such period to begin on either January 1 or July 1 of any year. In addition a town or city which adopts the appendix must provide training to the building official. If you have comment or questions on this subject please forward them to mike.quigli@state.ma.us

Appendix 120 AA July 9, 2009 Final FOF (270kb)

Stretch Code Overview June 5, 2009 FOF (66kb)

S	EARCH	
ı	Public Safety	V
S	Search	

## Questions?

### **Contacts:**

Dept. of Public Safety
Mike Guigli (617) 826-5215
mike.guigli@state.ma.us

Dept. of Energy Resources
Ian Finlayson (617) 626-4910
ian.finlayson@state.ma.us

Energy & Environment (EOEEA)
Marc Breslow (617) 626-1105
marc.breslow@state.ma.us

